



主要参数 / Main Specifications

型号 Model	单位 Unit	参数 Parameters
操作重量 Operation Weight	kg	21900
铲斗容量 Bucket Capacity	m ³	0.9-1.0

发动机 Engine

发动机型号 Model	/	ISUZU CC-6BG1TRP
电喷 Electronic fuel injection	/	√
4冲程 Four strokes	/	√
水冷 Water cooling	/	√
涡轮增压 Turbo-charging	/	√
空空中冷 Air to air intercooler	/	√
缸数 No. of cylinders	/	6
额定输出功率/转速 Output power	kW/rpm	128.5/2100
最大扭矩/转速 Torque/speed	N.m/rpm	637/1800
排量 Displacement	L	6.494

主要性能 Main performance

行驶速度(高低) Travel speed (H/L)	km/h	5.5/3.3
回转速度 Rotating speed	r/min	13.3
爬坡能力 Gradeability	°	≤35
接地比压 Ground pressure	kPa	47.2
铲斗挖掘力 Bucket digging force	kN	149
斗杆挖掘力 Arm digging force	kN	111
最大牵引力 Maximum traction	kN	184

液压系统 Hydraulic system

主泵 Main pump	/	2个柱塞泵
主泵额定流量 Rated flow of main pump	L/min	2 × 209
主安全阀压力 Pressure of prime valve	MPa	34.3/37.0
行走系统压力 Pressure of travel system	MPa	34.3
回转系统压力 Pressure of swing system	MPa	28
先导系统压力 Pressure of pilot system	MPa	3.9

油类容量 Oil capacity

燃油箱容量 Fuel tank capacity	L	400
液压油容量 Hydraulic tank capacity	L	220
发动机油容量 Engine oil capacity	L	25

型号 Model	单位 Unit	参数 Parameters
----------	---------	---------------

外形尺寸 Appearance size

A 总长 Overall length	mm	9625
B 总宽 Overall width	mm	2990
C 总高 Overall height	mm	3100
D 转台宽度 Width of platform	mm	2830
E 履带长度 Length of crawler	mm	4255
F 底盘总宽 Overall width of chassis	mm	2990
G 标准履带板宽度 Width of crawler	mm	600
H 履带轴距 Track length on ground	mm	3462
I 轨距 Crawler gauge	mm	2390
J 配置离地间隙 Clearance under counterweight	mm	1050
K 最低离地间隙 Min. ground clearance	mm	485
L 尾部回转半径 Min. tail swing radius	mm	2890

工作范围 Working scope

A 最大挖掘高度 Max. digging height	mm	9820
B 最大卸载高度 Max. dumping height	mm	6780
C 最大挖掘深度 Max. digging depth	mm	6680
D 8英尺水平面挖掘深度 Excavation depth of 8 feet level	mm	6500
E 最大垂直挖掘深度 Max. vertical wall digging depth	mm	5715
F 最大挖掘半径 Max. digging reach	mm	9940
G 最小回转半径 Min. swing radius	mm	3530

标配 Standard

动臂长度 Boom length	mm	5680
斗杆长度 Arm length	mm	2910
斗容 Bucket Capacity	m ³	1.0

选配 Optional

斗杆长度 Arm length	mm	5680
斗容 Bucket Capacity	m ³	1.0土方斗 1.0 Earth working bucket
	m ³	0.9岩石斗 0.9 Rock bucket

材料规格可随时间改变，恕不另行通知。
Materials and specifications may be changed at any time without prior notice.

XCMG
徐工集团

徐工徐工 助您成功
XCMG FOR YOUR SUCCESS

XE215C 液压挖掘机
XE215C HYDRAULIC EXCAVATOR



- 铲斗容量 Bucket Capacity (m³) : 0.9-1.0
- 操作重量 Operation Weight (kg) : 21900
- 额定功率 Output power (kW/rpm) : 128.5/2100

XCMG

地址: 徐州经济技术开发区高新路39号
Address: No.39 Gaoxin Road Economy Technology Development Zone Xuzhou
全国统一客服热线
Customer service hotline: 400-110-9999

WWW.XCMG.COM



XCMG1795

徐工挖掘机事业部
XCMG EXCAVATOR MACHINERY BUSINESS DEPARTMENT