



HX135G

Low Consumption, High Efficiency, Fuel Efficiency

Rated Power 74kW/2,200rpm

Operating Weight 13,800kg

Bucket Capacity 0.56m³

Main Technical Parameters

Engine	Manufacturer	-	Weichai(STD)	Yuchai(OPT)
	Model	-	WP4.1G100E440	YCF36125-T482
	Emission standard	-	Tier 4	
	Rated power(net)	kW/hp/ps/rpm	74/2200	92/2200
	Max. torque	N.M/rpm	420/1400~1600	480/1300~1600
	Piston displacement	cc	4088	
	No.of cylinder-bore×stroke	EA-mm	4-105×118	4-98×120
	Battery	EA - V x AH	2-24x100	
	Starting motor	V/kW	24/4.5	
	Alternator	V/A	28/55	
	Specifications	Swing speed	rpm	10.6
Swing torque		kN.m	40	
Travel speed		km/hr	3.6/5.6	
Gradeability		deg	35	
Max.drawbar pull		ton	11.5	
Bucket digging force(LOS)		ton	9.9	
Arm digging force(LOS)		ton	7.6	
Working Device	Boom Length/OPT	mm	4600	
	Arm length/OPT	mm	2500	
	Bucket Capacity/OPT(SAE)	m ³	0.56	

Dimensions	Overall length	mm	7880
	Overall width	mm	2500
	Upper width (Frame width)	mm	2500
	Overall height of boom (with hose)	mm	2865
	Overall height of cab	mm	2877
	Track gauge	mm	1990
	Tumbler distance(Wheelbase)	mm	3010
	Overall length of crawler	mm	3778
	Track shoe width(OPT)	mm	500
	Min.ground clearance	mm	422
	Ground clearance of counterweight	mm	903
	Tail swing radius/Tail radius	mm	2559/2520
Fuel Tank	Fuel tank	l	290
	Hydraulic tank(System)	l	200
	Engine oil	l	12