



混凝土泵车XS43

Truck mounted concrete Boom Pump XS43

Specifications

类别 Category	项目 Item	单位 Unit	XS43
整车参数 Overall parameter	外形尺寸 Outline dimension	mm	11120×2500×3930
	整机重量 Overall weight	kg	30000
底盘 Chassis	型号 Model		ZZ5337THBN464GE1 (R)
	生产厂家 Manufacturer		Sinotruk
	最高速度 Max.speed	km/h	89
	最大爬坡度 Max.grade-ability	%	35
	轴距 Wheelbase	mm	4400+1400
	轮胎规格 Tire		315/80R22.5(20PR),295/80R22.5(18PR)
发动机 Engine	型号 Model		MC07H.35-50
	最大功率 Max. power	kw	257
	最大扭矩 Max. torque	N·m/(r/min)	1400/(1200-1600)
	排量 Displacement	L	7.36
	排放标准 Emission standard		Euro III
泵送系统 Pumping system	理论输送量 Theoretical output	m³/h	130
	泵送压力 Concrete pumping pressure	MPa	8
	理论泵送次数 Theoretical pumping times	Time/min	23 ~ 26
	输送缸内径 × 行程 Delivery cylinder diameter × stroke	mm	φ230×1600
	泵送混凝土骨料最大直径 Max. diameter of pumping concrete aggregate	mm	40
	上料高度 Filling height	mm	1580
	泵送混凝土塌落度范围 Concrete slump range	cm	8 ~ 23
布料杆 Placing boom	布料杆可达高度 Reach height	m	42.1
	布料杆可达深度 Reach depth	m	29
	布料杆回转半径 Slewing radius	m	37.3
	布料杆回转角度 Slewing angle	°	360
	第一节臂伸展角度 Unfolding angle of the 1st section	°	90
	第二节臂伸展角度 Unfolding angle of the 2nd section	°	180
	第三节臂伸展角度 Unfolding angle of the 3rd section	°	180
	第四节臂伸展角度 Unfolding angle of the 4th section	°	230
	第五节臂伸展角度 Unfolding angle of the 5th section		210
支腿跨距 Stabilizer span	支腿纵向跨距 Longitudinal span of stabilizer	mm	7400
	前支腿横跨距 Transverse span of front stabilizer	mm	7410
	后支腿横跨距 Transverse span of rear stabilizer	mm	7730
其它 Others	配料型式 Transfer tube		Rock valve /S valve
	润滑方式 Lubrication method		自动润滑 Automatic lubrication
	控制方式 Control method		手动 / 遥控 Manual/remote control
	水箱容积 Volume of water box	L	400

Specifications subject to change without prior notice. Photos for illustrative purpose only.

